


Drive Cage *Standard 3.5" Device in 5.25" Drive Bay Solutions*

Following the traditional industrial system needs for stability, durability and toughness for storage drive operating condition, IEI provides various kinds of standard 3.5" device in 5.25" removable drive bay and modules for different demands.

	SATA / IDE / SSD Solution		SATA Solution	
				
Model Name	XWC-410030507220-RS	XWC-410030507230-RS	RD-03A-R20	RHD-302SATA-R20
Dimensions (L x W x H) (mm)	150 x 146 x 42	150 x 146 x 42	186 x 146 x 42	202 x 146 x 86
Material	Aluminum	Aluminum	Aluminum alloy	Aluminum alloy
Interface	SATA / IDE / SSD	SATA / IDE / SSD	SATA III / SAS 2.0	SATA III / SAS 2.0
Data Transfer Rate			SAS 2.0 / SATA III 6Gbps	SAS 2.0 / SATA III 6Gbps
Drive Bay Space	One 5.25" drive bay	One 5.25" drive bay	1 x 5.25" Device Bay for 1 x 2.5" or 3.5" Hard Drive	2 x 5.25" Device Bay for 3 x 2.5" or 3.5" Hard Drive
HDD Type	Internal 3.5" device bay	Internal 3.5" device bay	2.5" or 3.5" Hard Drive	2.5" or 3.5" Hard Drive
Cooling Fan			8CM	8 cm
Hot Swap	No	No	Yes	Yes
Keylock	No	No	No	No
Signal Out	No	No	SATA III 7-Pin	SATA III 7-Pin
Color	Black	White	Black	Black
Gross Weight	0.2 kg	0.2 kg	0.85kg	1.3kg

	SATA Solution				
					
Model Name	RHD-102SATA-R20	RHD-102DW-R20	RHD-101SATA-R20	RHD-104SATA-R20	RHF-21-SATA-R10
Dimensions (L x W x H) (mm)	140 x 101.6 x 25	153 x 146 x 42	140 x 101.6 x 25	149.6 x 146 x 42.1	151.5 x 102 x 25.7
Material	Aluminum & SPCC	Aluminum	Aluminum & SPCC	Full Metal	SECC
Interface	SATA 7 + 15 Pin	SATA	SATA 7 + 15 Pin	SATA III	SATA
Data Transfer Rate	up to 6Gb/Sec	up to 6Gb/Sec	Up to 6Gb/Sec	SATA III 6Gbps	No
Drive Bay Space	One 3.5" drive bay	One 5.25" drive bay	One 3.5" drive bay	1 x 5.25" Device Bay for 4 x 2.5" Hard Drive	Internal 3.5" drive bay
HDD Type	2.5" SATA/SAS 2 x HDD/SSD	2.5" SATA 2 x HDD/SSD	2.5" SATA/SAS 1 x HDD/SSD	2.5" Hard Drive	2.5" SATA HDD
Cooling Fan	No	Yes	No	4CM	No
Hot Swap	Yes	Yes	Yes	Yes	Yes
Keylock	Yes	Yes	Yes	Yes	Yes
Signal Out	SATA 7 Pin	SATA 7 Pin	SATA 7 Pin	SATA III 7-Pin	1 x Female connector 1 x SATA LED signal connector 1 x Power LED connector 1 x Key on/off connector 1 x Power/SATA LED connector 1 x Male connector
Color	Black	Black	Black	Black	Black
Gross Weight	0.304 Kg	0.534 Kg	0.236 Kg	0.56kg	0.3 kg

FCD-301



Pin 1	Pin 2	Pin 3	Pin 4
+5V	Data-	Data+	GND

3.5" compact drive bay with USB port

- The most suitable USB cable for IEI's CPU boards
- Support standard 3.5" drive bay, 4-pin female connector to CPU boards' pin header, length: 60cm
- RoHS compliant
- Pin definition:

Ordering Information

Part No.	Description
FCD-301[C]-RS	3.5" compact drive bay with USB port, RoHS Color Code: B=Black, W=White


AS-35A / AS-25A / AS-25C



AS-35A

AS-25A

Anti-vibration Drive Kit



AS-25C

- Resistant to shocks and vibrations from all directions
- Support 2.5" HDD into 3.5" drive bay (AS-25A/ 25C)
Support 3.5" HDD into 5.25" drive bay (AS-35A)
- Meets the following standards:
 - MIL-SLD-810F 514.5C-1 standard
 - 5-20Hz, 1G peak to peak
 - 60-200Hz, 3G peak to peak
- RoHS compliant

Ordering Information

Part No.	Description
AS-35A-RS	3.5" drive anti-vibration kit, RoHS
AS-25A-RS	2.5" drive anti-vibration kit, RoHS
AS-25C-RS	Enhanced 2.5" drive anti-vibration kit, RoHS

Industrial Keyboard Series

MK-KTP5A



Model Name	MK-KTP5AW-RS-R11		
Key Number	105-key	Color	White/Black
Mouse	Touchpad	Waterproof	NA
Connector	2 x PS/2 for KB/MS	Dimensions (mm)	485 (D) x 380 (W) x 44 (H)

Ordering Information

Part No.	Description
MK-KTP5AW-RS-R11	1U rackmount keyboard/touchpad drawer, RoHS